



Via Geretta 11
22037 Pontelambro(Como) Italia
TEL.031/623380
FAX 031/622554
e-mail: info@fas-selvitex.com
<http://www.fas-selvitex.com>



SCHEMA TECNICA ART. ZERMA 300 SPALMATO PVC
DATA SHEET ZERMA 300 PVC BACKING
FICHA TECNICA ZERMA 300 PLASTIFICADO PVC

TESSUTO(FABRIC/TEJIDO) : 100 % POLIESTERE

SPALMATURA(COATING/ACABADO) : P.V.C.

PESO TESSUTO FINITO(TOTAL WEIGHT/PESO TEMINADO) : GR.350 MT2 (+/- 5%)

ALTEZZA TESSUTO(WITH/ANCHO) : CM 150-160

ROTOLE (ROLLS/ROLLOS) : MT.60

NUMERO FILI AL CM (YARN FOR CM/HILOS AL CM): ORDITO 22(+/-2) TRAMA 18 (+/-2)

RESIST. LACERAZIONE(UNI EN 4818 : 1992 P.TE 9) ORD. N 140 (+/- 5%) TRAMA N 125 (+/- 5%)
(TEAR RESISTENCE/RESISTENCIA AL DESGARRE)

RESIS.ROTTURA(UNI 13934-1 :2000) ORD. N 1300 (+/- 5 %) TRAMA N.1100 (+/- 5%)
(HIGHEST STRENGHT/RESISTENCIA A LA ROPTURA)